

**PT  
Range**

**Portable Tool  
Transformers**



**Product Data Sheet 404/2 Issue 1**

## **PORTABLE TOOL TRANSFORMERS**

### **350 VA - 3 kVA CONTINUOUS RATING**

*All transformers encapsulated in splash proof case made of self extinguishing grade glass fibre reinforced polyester compound. The cases, with carrying handle, have 1.5 m three core cable fitted and output sockets to BSEN 60309-2: 1999 (BS 4343).*

*The transformers are double wound with earth screen and are protected by thermal cut out with manual reset.*

*Custom built portable tool transformers are available at other voltages and higher VA ratings.*



**Portable Tool Transformer  
with two output sockets**

<b>PRODUCT REFERENCE</b>	<b>CONTINUOUS RATING</b>	<b>30 MINUTE RATING</b>	<b>WEIGHT kg</b>	<b>No. OF SOCKETS</b>
PT/350/1	350 VA	500 VA	6	1
PT/750/1	750 VA	1 kVA	9	1
PT/750/2	750 VA	1 kVA	9	2
PT/1k/1	1 kVA	2 kVA	11	1
PT/1k/2	1 kVA	2 kVA	11	2
PT/1.5k/2	1.5 kVA	2.5 kVA	16	2
PT/2k/2	2 kVA	3 kVA	23	2
PT/3k/2	3 kVA	4 kVA	34	2

**THE STANDARD PORTABLE TOOL INPUT VOLTAGE IS 240 VAC**

**OUTPUT 55 - 0 - 55 VAC**

**OTHER VOLTAGES AND VA RATINGS ARE AVAILABLE AS CUSTOM BUILT UNITS**